



UNITCARD

225K QUICK RIG

Service -> Hydraulic Workover -> Equipment



Fast, reliable and safe best describe the 225K Snubbing Unit's key benefits. The compact design is ideally suited for moving quickly from site to site. It's rapid rig-up time make it a very efficient option. Easily rigged up in two lifts, this versatile snubbing unit is ideal for onshore applications and is extremely well suited for through tubing live well work like; wireline/coil tubing fishing, velocity strings and well clean-outs.

The Practical slim line design of the jack has resulted in faster jack speed and increasing the trip time ensuring less time is spent on the well; this is significant, as it reduces cost. A Special Annular BOP window enables quick annular rubber change-outs without the need of rigging down the unit.

Advantages & Characteristics:

- ✓ Trailer mounted | Installation in two lifts
- ✓ 7-1/16" BOP Stacks with stripping annular
- ✓ Flexible BOP Stack heights
- ✓ Mobile
- ✓ Excellent cost-quality ratio
- ✓ Multi-purpose application

Technical Data

Max. pull capacity	225,000 lbs	100.000 kg
Max. push capacity	90,000 lbs	40.000 kg
Rotary torque	6,000 ft @ 140RPM	8.000 Nm @ 140RPM
Stroke	10 ft	3 m.
Through bore	11 1/8"	11 1/8"
Gin pole	2 x 3,000 lbs	2 x 1.300 kg
	2 x 8,000 lbs	1 x 3.500 kg (main winch)
Unit total weight	57,000 lbs	26.000 kg