



UNITCARD

340K HWO/Snubbing unit

Service -> Hydraulic Workover -> Equipment



The reliable and flexible 340K HWO/Snubbing Unit has been designed for all well situations; live/dead, onshore/offshore. The 340K satisfies in your need for high quality-, safe and efficient Snubbing or Workover operations in any environment.

The jointed work string is handled by means of 4 hydraulic cylinders (3m stroke). The use of hydraulic cylinders allows perfect control over work string movements and makes it easy to use all types of downhole tools.

Technical Data

Max. pull capacity	340,000 lbs	100.000 kg
Max. push capacity	166,000 lbs	40.000 kg
Rotary torque	20.000 ft lbs	27.000 Nm
Stroke	10 ft	3 m.
Through bore	11 1/8" (Snubbing)	283 mm (Snubbing)
	13 5/8" (HWO)	346 mm (HWO)
Slip bowls	600,000 lbs	270.000 kg
Gin Pole	2 x 3,300 lbs	2 x 1.500 kg
Unit total weight	80,000 lbs	40.000 kg

Operational Activities:

- Handling all types of completions
- Live/dead well operations
- Packer setting/milling
- Well clean out
- Live well Fishing operations
- Underbalance installation of liners
- Remedial operations
- Installation of Velocity Strings

Advantages & Characteristics:

- Unique "Slip bowl interlock system"
- Small footprint
- Flexible
- Mobile
- Excellent cost-quality ratio
- Multi-purpose application