



UNITCARD

600K HWO/Snubbing Unit

Service -> Hydraulic Workover -> Equipment



The reliable and flexible 600K HWO/Snubbing Unit has been designed for all well situations; live or dead well and onshore or offshore jobs. The 600K satisfies in you needs for high quality, safe and efficient Snubbing or Workover operations in any environment.

The jointed work string is handled by means of 4 hydraulic cylinders (3m stroke). The use of hydraulic cylinders allows perfect control over work string movements and makes it easy to use all types of downhole tools.

Technical Data

Max. pull capacity	600,000 lbs	270.000 kg
Max. push capacity	263,000 lbs	118.000 kg
Rotary torque	20,000 ft lbs	27.000 Nm
Stroke	10 ft	3 m.
Through bore	13 5/8" (HWO)	346 mm (HWO)
	11 1/8" (Snubbing)	283 mm (snubbing)
Slip bowls	600.000 lbs	270.000 kg
Gin pole	2 x 5,500 lbs	2 x 2.500 kg
Unit total weight	80,000 lbs	40.000 kg

Operational Activities:

- Handling all types of completions
- Live/Dead well operations
- Live well Fishing operations
- Packer setting/milling
- Remedial operations
- Well clean out
- Installation of velocity strings

Advantages & Characteristics:

- Unique "Slip bowl Interlock System"
- Small footprint
- Flexible
- Mobile
- Excellent cost-quality ratio
- Multi-purpose application